

Электродвигун АИР 112М2 7,5 кВт 3000 об/мин IM 3081

Technical drawing of the 1000L model, showing front, top, and side views with dimensions:

- Front View:**
 - Overall height: 1300(L)
 - Top width: 630(A)
 - Bottom width: 624(P)
 - Bottom depth: 620(N)
 - Base width: 630(R)
 - Base depth: 115(E)
 - Top panel height: 120(T)
 - Top panel width: 622(S)
 - Top panel depth: 620(W)
 - Top panel angle: 45° (10-4)
 - Top panel radius: (R10) 5' 22"
- Top View:**
 - Overall width: 630(A)
 - Overall depth: 620(W)
 - Top panel width: 622(S)
 - Top panel depth: 620(W)
 - Top panel angle: 45° (10-4)
 - Top panel radius: (R10) 5' 22"
- Side View:**
 - Overall height: 1300(L)
 - Top width: 630(A)
 - Bottom width: 624(P)
 - Bottom depth: 620(N)
 - Base width: 630(R)
 - Base depth: 115(E)
 - Top panel height: 120(T)
 - Top panel width: 622(S)
 - Top panel depth: 620(W)
 - Top panel angle: 45° (10-4)
 - Top panel radius: (R10) 5' 22"

Монтажное исполнение 3081

Головний енергетик Першотравневого кар'єру

І.А. Синельник

15.11.23p.