


Позитивные круглые пластины с задним углом 7°



Размер	Размеры (мм)	
	d	t
08	8.0	3.18
10	10.0	3.18-3.97
12	12.0	4.76
16	16.0	6.35
20	20.0	6.35
25	25.0	7.94
32	32.0	9.52

Пластина	Обозначение	Подача (мм/об)	ap (мм)	Кермет	CVD покрытие										PVD покрытие		Без покрытия								
					PV3010 CT3000	TT7005	TT7015	TT7310	TT8105	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20	
 Получистовая	RCMT 080300 MT	0.15-0.40	0.5-3.0																						
	10T300 MT	0.20-0.50	1.0-4.0			•				•	•					•									
	120400 MT	0.30-0.60	2.0-5.0			•	•	○		•	•														
	160600 MT	0.40-0.80	3.0-7.0								•														
 Чистовая	RCMT 120400 PC	0.30-0.60	2.0-5.0							•	•						•								
 Черновая	RCMX 100300	0.25-0.50	1.5-4.0			•	○		•	•						•									
	120400	0.30-0.60	2.5-5.0						•	•						•									
	160600	0.40-0.75	3.0-7.0			•	•		•	•						•							•		
	200600	0.48-0.90	3.5-9.0			•	•	○	•	•	•														
	250700	0.55-1.20	4.0-12.0			•	•	○	•	•							•								
	320900	0.65-1.50	5.0-15.0						•	•															
 Черновая	RCMX 100300 RA	0.20-0.50	1.0-4.0							•	•														
	120400 RA	0.25-0.60	2.0-5.0							•	•	•													
	160600 RA	0.35-0.75	2.5-7.0							•	•	•													
	200600 RA	0.40-0.90	3.0-9.0							•	•														
	250700 RA	0.50-1.20	3.5-12.0							•	•														
	320900 RA	0.60-1.50	4.0-15.0								•														



A77, A78,
A90, A135,
A153

taeguTec
CORPORATION

●: Стандартные позиции
○: Полустандартные позиции