



PLUG-IN RELAY COMPLETE UNIT AC 230V,
4 CO CONTACT LED MODULE RED STANDARD PLUG-IN
SOCKET SCREW TERMINAL 3.5 MM PINNING

General technical details:		
Supply voltage frequency / for auxiliary and control current circuit / rated value		
• minimum	Hz	50
• maximum	Hz	60
type of voltage		AC
Control supply voltage		
• at 50 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
• at 60 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
Number of NC contacts		
• for auxiliary contacts		0
Number of NO contacts		
• for auxiliary contacts		0
Number of change-over switches		
• for auxiliary contacts		4
Operating current / of the auxiliary contacts		
• at DC-13		

• at 24 V	A	6
• at AC-15		
• at 230 V	A	4
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		Yes
Width	mm	28
Height	mm	72
Depth	mm	74

Certificates/approvals:

General Product Approval	other
	<u>Declaration of Conformity</u>

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZS:PT5A5T30/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:PT5A5T30

last change:

Oct 24, 2011